



IN STOCK — FOR SALE

Featured at IPF'08 (Japan)
In Showroom Condition

UNDERWATER PELLETIZING SYSTEM

Capacity Rate: 340—400 kg/h
Material Application: PE, PP, EVA, PET, TPU,
ABS, PS, Masterbatch and more
Pellet Size: 0.30 mm to 12.0 mm
Power: 380VAC, 50 Hz, Non-Hazardous Area

INCLUDES:

- 90 mm Extruder; 30:1 L/D, non-vented, air-cooled
- Adapters
- Sliding Plate, discontinuous Screen Changer with HPU
- Polymer Diverter Valve, side discharge
- Water Box By-pass Piping Assembly
- MAP-6 Underwater Pelletizer
- TWS-80 Tempered Water System with Model 2008BF Dryer
- Touch Screen Control System

ADVANTAGES

- Use with wide range of applications and pellet sizes
- Pre-wiring and pre-piping included
- Quick disconnect plugs
- Compact design (skidded) - very little space
- Mobile capability
- Fully automated & interlocked
- Graphic design touch screen
- Remote control station



QUALITY · INNOVATION · COMMITMENT · SERVICE

[CLICK HERE](#) for more information!

GALA INDUSTRIES, INC.
181 Pauley Street, Eagle Rock, VA 24085 USA Tel: (540) 884-2589 · Fax: (540) 884-2310
www.Gala@gala-industries.com · www.gala-industries.com